


INGROUND UPLIGHTER

RAY

F25-104110



A = 4-1/16 in (104 mm) | B = 4-5/16 in (110 mm) | C = 3-1/4 in (83 mm) | D= 19-11/16 in (500 mm)


PRODUCT FEATURES



DESCRIPTION

Architectural grade linear inground uplighters featuring a stainless steel trim and aluminum body, designed with high-output COB LEDs and precision optics to deliver uniform vertical illumination. Engineered for facade washing and grazing applications, they provide consistent lighting for building facades, columns, and landscape structures. Available in narrow to wide beam angles to suit various architectural lighting requirements.

LIGHT DISTRIBUTION



ACCESSORIES

Optical Accessories

- Clear glass
 - Honeycomb Louver
- Frosted glass

Back Box Materials

- Aluminium

FINISHES



Steel Brush

PRODUCT PARAMETER

Power	Input Voltage	Beam Angle	CRI	CCT	Control Type	Finishes	IP Rating	
4W	DC 24V	6°	90-Ra>90	2700K	ON/OFF	Steel Brush	IP-67	
	DC 12V	15°	85-Ra>85	3000K	PHASE			
		24°		4000K	DALI			
		36°		6000K	DMX			
		60°						
		Asymmetric						

**Please provide the specific details based on the requirements for the products you are ordering.